


RD-18B-S003 Specifications


寸法 Dimensions



A	12.5
B	2.3
C	1.4
D	7.5
E	2.0
F	1.2


項目 Item		RD-18B-S003
接点 Contact	接点タイプ Contact type	1A
	接点材料 Contact material	ルテニウム Ruthenium
電气的特性 Electrical characteristics	感働値 Pull In Value	10-30AT
	※加工前感度	※before modifying
	開放値 Drop Out Value(Min.)	5AT
	※加工前感度	※before modifying
	最大開閉電力	1W
	Maximum switching electric power	
	最大開閉電圧	30VDC
	Maximum switching voltage	
	最大開閉電流	0.1A
	Maximum switching current	
動作特性 Operating characteristics	最大通電電流	0.3A
	Maximum carry current	
	接点接触抵抗 Contact resistance	250mΩ
	耐電圧 Breakdown voltage	200VDC(min.)
その他 Others	寿命 Life	1×10 ⁷ (5VDC,10mA)
	コイル Standard Coil	N-104
	特徴 Features	極超小型、表面実装型 Super ultra miniature、SMT

テープ寸法



シリーズ名	A	B	W	F	E	G	D1	P1	P2	P0	D0	T1	T2
RD-18B	2.0	13.2	24.0	11.5	1.75	—	—	8.0	2.0	4.0	1.55	0.3	(3.0)
RD-7B	4.0	20.3	32.0	14.2	1.75	28.4	1.55 × 1.75	8.0	2.0	4.0	1.55	0.3	(3.0)
NRS-701	2.7	16.6	24.0	11.5	1.75	—	—	8.0	2.0	4.0	1.55	0.4	(3.2)

リール寸法



シリーズ名	A	B	C	W
RD-18B	250	100	13	24.5
RD-7B	330	100	13	33.5
NRS-701	330	80	13	24.5